



pure data for a **healthy** planet.

Quoted by:

YSI

To: David Lee

4500 Mykonos Way

Elk Grove, CA 95758-7003 Phone: 916-421-5199 Quote # 000084

Tr YSI Date: 4/14/2005

Valid through: 5/14/2005

Line #	Part#	Description	Retail	Qty	Extend
1	6600E-02	6600-EDS-M Multi-Parameter Water Quality Logger EDS = Extended Deployment System Featuring "Wiped" Rapid Pulse D.O. Technology Includes:  - Medium depth (0-200 ft)  - Stainless steel bulkhead connector  - 384K Flash Memory  - RS-232 and SDI-12 communications interfaces  - Stainless steel waterproof bulkhead connector  - Stainless steel lifting bail  - Sensor guard  - 6560 Conductivity/Temperature Probe Kit  - 6570 Maintenance Kit  - Calibration cup  - Transport cup  - EcoWatch for Windows software  - Operations manual  - Operates from 8 - "C" cells, included	\$6,090.00	1	\$6,090.00
2	006562	6562 DO Field Replaceable 6-Series Probe Kit Dissolved Oxygen: Range: 0 - 50 mg/L Resolution: 0.01 mg/L Accuracy: +/- 2% of reading or 0.2 mg/L	\$500.00	1	\$500.00
3	605091	6561FG Flat Glass pH Probe Kit for EDS - for use on 6600EDS pH: Range: 0 - 14 units Resolution: 0.01 units Accuracy: +/- 0.2 unit	\$210.00	1	\$210.00
4	606136	6136 Turbidity Probe Type: Nephlometric (90 degree scatter) Range: 0-1000 NTU	\$1,340.00	1	\$1,340.00



Page 1

Page Sub-Total

\$8,140.00


Find out at www.YSI.com

**YSI Incorporated** 

1725 Brannum Lane

Yellow Springs, OH 45387

Ph: (800) 897-4151 Fax: (937) 767-1058 support@ysi.com



## YSI Environmental



pure data for a **healthy** planet.



Quote # 000084

Quoted by:

Date: 4/14/2005

Valid through: 5/14/2005

					3/14/2003
Line #	Part#	Description	Retail	Qty	Extend
		Accuracy: +/- 5% or 2 NTU Resolution: 0.1 NTU Maximum operating depth: 0 to 200 feet Cleaning: Automatic, mechanical wiper			
5	606025	6025 Fluorescence Chlorophyll Probe Assembly Features: - LED light source 465 nm emission - Automatic, self-cleaning, mechanical wiper - Photodetector picks up "fluorescence" at 680 nm wavelength Specifications: Range: 0-200 microgram/L as chlorophyll 0-100% as fluorescence Resolution: 0.1 microgram/L Chl; 0.1% FS Operating Pressure: 66 meters (216 feet) Operating Temperature: -5 to 45°C	\$2,630.00	1	\$2,630.00
6	006092	6092 50 ft Field Cable - Urethane jacketed - Kevlar reinforced - Chinese finger strain relief	\$500.00	1	\$500.00
7	650-04	650 Multiparameter Display System Model 650 Instrument with High Memory, with Barometer Specifications: - Size: 4.7"W X 9"L (11.9 X 22.9 cm) - Display: ¼ VGS; LCD with 320 by 240 pixels with backlight - Power: 4 Alkaline C Cells with detachable battery cover - Optional Battery Configuration: Ni Metal Hydride Battery Pack with attached battery cover and 110 volt charging system - Waterproof: IP 67 for both the standard alkaline battery configuration and for the rechargeable battery pack option - Operating Temperature Range for Visible Display: -10 to 60°C - Storage Temp Range: -20 to 70°C - Weight with Batteries: 2.1 lbs - Communication Protocol: RS-232 to all sondes and for data transfer to PC and	\$2,500.00	1	\$2,500.00











Quoted by:

Date:

4/14/2005

Valid through:

5/14/2005

Description	Retail	Qty	Extend
for software updates - Optional GPS: Y-cable - NMEA 0183 - Standard Backlight Feature: 4 LEDs illuminating LCD; user selectable - Keyboard: 20 keys including instrument On/Off, Backlight On/Off, Enter, Esc, 10 Number/Letter Entry Keys, 2 Vertical arrow keys, 2 Horizontal arrow keys, minus key, and a decimal point key Connector: MS-8; Meets IP 67 specification - Memory: high memory with more than 50,000 data sets			
6067B Dry calibration cable - Leave it connected to PC - Lab or office use only	\$180.00	1	\$180.00
	for software updates - Optional GPS: Y-cable - NMEA 0183 - Standard Backlight Feature: 4 LEDs illuminating LCD; user selectable - Keyboard: 20 keys including instrument On/Off, Backlight On/Off, Enter, Esc, 10 Number/Letter Entry Keys, 2 Vertical arrow keys, 2 Horizontal arrow keys, minus key, and a decimal point key Connector: MS-8; Meets IP 67 specification - Memory: high memory with more than 50,000 data sets  6067B Dry calibration cable - Leave it connected to PC	for software updates - Optional GPS: Y-cable - NMEA 0183 - Standard Backlight Feature: 4 LEDs illuminating LCD; user selectable - Keyboard: 20 keys including instrument On/Off, Backlight On/Off, Enter, Esc, 10 Number/Letter Entry Keys, 2 Vertical arrow keys, 2 Horizontal arrow keys, minus key, and a decimal point key Connector: MS-8; Meets IP 67 specification - Memory: high memory with more than 50,000 data sets  6067B Dry calibration cable \$180.00 - Leave it connected to PC	for software updates - Optional GPS: Y-cable - NMEA 0183 - Standard Backlight Feature: 4 LEDs illuminating LCD; user selectable - Keyboard: 20 keys including instrument On/Off, Backlight On/Off, Enter, Esc, 10 Number/Letter Entry Keys, 2 Vertical arrow keys, 2 Horizontal arrow keys, minus key, and a decimal point key Connector: MS-8; Meets IP 67 specification - Memory: high memory with more than 50,000 data sets  6067B Dry calibration cable - Leave it connected to PC

Quote # 000084

SHIPMENT: 4 to 6 weeks after receipt of order Page Sub-Total

TERMS: Purchase order or pre-payment

Net 30 Days

F.O.B. Yellow Springs, OH, U.S.A. MasterCard and Visa are also accepted.

FREIGHT: Prepaid and Added to Invoice - Amount TBD

Your local YSI representative is:

Total =

**Sub-Total** 

\$13,950.00

\$180.00

\$13,950.00

David Lee

Western Region Manager